

SAFETY DATA SHEET

AGS 60

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

AGS 60

Product no.

3660

1.2. Relevant identified uses of the substance or mixture and uses advised against

▼ Relevant identified uses of the substance or mixture

Graffiti shadow remover

Restricted to professional users.

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Trion Tensid AB

Svederusgatan 1-3

SE-75450 Uppsala

Sweden

+46 18 15 61 90

www.trion.se

Contact person

William Stomilovic

E-mail

info@trion.se

Revision

11/11/2024

SDS Version

4.0

Date of previous version

29/09/2022 (3.0)

1.4. ▼Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)

General public:

England - Dial 111 to reach NHS 111 (24 hour service)

Scotland - Dial 112 to reach NHS 24 (24 hour service)

Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)



See section 4 "First aid measures".

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. Classification of the substance or mixture

Skin Corr. 1; H314, Causes severe skin burns and eye damage.

Eye Dam. 1; H318, Causes serious eye damage.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Causes severe skin burns and eye damage. (H314)

Precautionary statement(s)

General

-

Prevention

Do not breathe vapour/mist. (P260)

Wear eye protection/protective gloves/protective clothing. (P280)

▼ Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. (P303+P361+P353)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)

Immediately call a POISON CENTER/doctor. (P310)

Storage

-

▼ Disposal

Dispose of contents/container in accordance with local regulation (P501)

▼ Hazardous substances

potassium hydroxide

hexyl D-glucoside

Additional labelling

Not applicable.

2.3. Other hazards

▼ Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification. This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.



SECTION 3: Composition/information on ingredients

3.1. ▼Substances

Not applicable. This product is a mixture.

3.2. ▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
potassium hydroxide	CAS No.: 1310-58-3 EC No.: 215-181-3 UK-REACH: Index No.: 019-002-00-8	10-15%	Acute Tox. 4, H302 Skin Corr. 1A, H314 Skin Corr. 1B, H314 (SCL: 2.00 %) Skin Irrit. 2, H315 (SCL: 0.50 %) Eye Irrit. 2, H319 (SCL: 0.50 %)	
1-methoxy-2-propanol monopropylene glycol methyl ether	CAS No.: 107-98-2 EC No.: 203-539-1 UK-REACH: Index No.: 603-064-00-3	5-10%	Flam. Liq. 3, H226 STOT SE 3, H336	[1]
hexyl D-glucoside	CAS No.: 54549-24-5 EC No.: 259-217-6 UK-REACH: Index No.:	3-5%	Eye Dam. 1, H318	
Alcohols, C9-C11, Ethoxylated	CAS No.: 68439-46-3 EC No.: 614-482-0 UK-REACH: Index No.:	3-5%	Eye Irrit. 2, H319	[19]
2-aminoethanol	CAS No.: 141-43-5 EC No.: 205-483-3 UK-REACH: Index No.: 603-030-00-8	<1%	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Acute Tox. 4, H332 STOT SE 3, H336 (SCL: 5.00 %)	[1]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

- [1] European occupational exposure limit.
- [19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.



Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Flush exposed area with water for a long time - at least 30 minutes. It may be necessary to flush for several hours. Use a comfortable water temperature (20-30 °C). Contact Poison Information/doctor/hospital for further advice on follow-up and treatment.

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

▼ Eye contact

If in eyes: Flush eyes with plenty of water or salt water (20-30 °C) for at least 30 minutes and continue until irritation stops. Remove contact lenses. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.

▼ Ingestion

In the case of ingestion, contact a doctor immediately. If the person is conscious, give them water. DO NOT try to induce vomiting unless this is recommended by a doctor. Hold head facing down to prevent vomit from returning to the mouth and throat. Prevent shock by keeping the injured person warm and calm. Initiate immediate resuscitation if breathing stops. If unconscious, roll the injured person into recovery position. Call an ambulance.

Burns

Not applicable.

4.2. ▼ Most important symptoms and effects, both acute and delayed

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. ▼ Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2)

Some metal oxides

5.3. ▼Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact



The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

Hazchem Code: 2R

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. ▼ Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. ▼ Precautions for safe handling

Avoid direct contact with the product.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Always store in containers of the same material as the original container.

Storage conditions

4 - 25 Celcius

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. ▼ Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. ▼ Control parameters

potassium hydroxide

Short term exposure limit (15 minutes) (mg/m³): 2



1-methoxy-2-propanol monopropylene glycol methyl ether

Long term exposure limit (8 hours) (ppm): 100 Long term exposure limit (8 hours) (mg/m³): 375 Short term exposure limit (15 minutes) (ppm): 150

Short term exposure limit (15 minutes) (mg/m³): 560

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

2-aminoethanol

Long term exposure limit (8 hours) (ppm): 1 Long term exposure limit (8 hours) (mg/m³): 2,5 Short term exposure limit (15 minutes) (ppm): 3 Short term exposure limit (15 minutes) (mg/m³): 7,6 Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

▼ DNEL

2-aminoethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	0,24 mg/sqm
Long term – Systemic effects - Workers	Dermal	1 mg/kg/day
Long term – Local effects - General population	Inhalation	2 mg/kbm
Long term – Local effects - Workers	Inhalation	3,3 mg/kbm
Long term – Systemic effects - General population	Inhalation	2 mg/kbm
Long term – Systemic effects - Workers	Inhalation	3,3 mg/kbm
Long term – Systemic effects - General population	Oral	3,75 mg/kg

hexyl D-glucoside

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	357000 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	595000 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	124 mg/m3
Long term – Systemic effects - Workers	Inhalation	420 mg/m3
Long term – Systemic effects - General population	Oral	35,7 mg/kg bw/day

▼ PNEC

2-aminoethanol



Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		0,085 mg/L
Freshwater sediment		0,434 mg/kg
Intermittent release		0,028 mg/L
Marine water		0,0085 mg/L
Marine water sediment		0,0434 mg/kg
Sewage treatment plant		100 mg/L
Soil		0,0367 mg/kg
hexyl D-glucoside		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Single	0,176 mg/L
Freshwater sediment	Single	0,722 mg/kg
Marine water	Single	0,018 mg/L
Marine water sediment	Single	0,072 mg/kg
Marine water sediment Sewage treatment plant	Single Single	0,072 mg/kg 100 mg/L

8.2. ▼ Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

▼ Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Ensure that eyewash stations and safety showers are located within easy reach.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

▼ Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally

Wash contaminated clothing before reuse.

Use only UKCA marked protective equipment.



Respiratory Equipment

	Work situation	Туре	Class	Colour	Standards	
	In the event of insufficient ventilation	A	Class 1 (low capacity)	Brown	EN14387	
		Respiratory protection is not needed in the event of adequate ventilation	-	-	-	
Ski	n protection					
	Recommended	Type/Category		Standards		
	Dedicated work clothing should be	-		-		1

Hand protection

worn.

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0,4	>480	EN374-2	

ye protection		
Туре	Standards	
Wear safety glasses with side shields.	EN166	



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Tan

▼ Odour / Odour threshold

Solvent

рΗ

14

Density (g/cm³)

1.085

▼ Kinematic viscosity

No relevant or available data due to the nature of the product.



Particle characteristics

Does not apply to liquids.

Phase changes

▼ Melting point/Freezing point (°C)

No relevant or available data due to the nature of the product.

▼ Softening point/range (°C)

Does not apply to liquids.

▼ Boiling point (°C)

No relevant or available data due to the nature of the product.

▼ Vapour pressure

No relevant or available data due to the nature of the product.

▼ Relative vapour density

No relevant or available data due to the nature of the product.

▼ Decomposition temperature (°C)

No relevant or available data due to the nature of the product.

Data on fire and explosion hazards

Flash point (°C)

67

▼ Flammability (°C)

230

▼ Auto-ignition temperature (°C)

No relevant or available data due to the nature of the product.

▼ Lower and upper explosion limit (% v/v)

1.1 - 10.6

Solubility

Solubility in water

Completely soluble

▼ n-octanol/water coefficient (LogKow)

No relevant or available data due to the nature of the product.

▼ Solubility in fat (g/L)

No relevant or available data due to the nature of the product.

9.2. Other information

▼ Oxidizing properties

No relevant or available data due to the nature of the product.

▼ Other physical and chemical parameters

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.



10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. ▼ Hazardous decomposition products

Thermal decomposition may produce corrosive vapours.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

▼ Acute toxicity

Product/substance potassium hydroxide

Species: Rat
Route of exposure: Oral
Test: LD50
Result: 273 mg/kg ·

Product/substance 1-methoxy-2-propanol monopropylene glycol methyl ether

Species: Rat
Route of exposure: Oral
Test: LD50
Result: 7200 mg/kg

Product/substance 1-methoxy-2-propanol monopropylene glycol methyl ether

Species: Rabbit
Route of exposure: Dermal
Test: LD50
Result: 13000 mg/kg ·

Product/substance 1-methoxy-2-propanol monopropylene glycol methyl ether Species: Rat

Route of exposure: Inhalation
Test: LC 50 (6 Hours)
Result: 7200 ppm

Product/substance hexyl D-glucoside

Species: Rat
Route of exposure: Oral
Test: LD50
Result: >2000 mg/kg

Product/substance hexyl D-glucoside

Species: Rabbit
Route of exposure: Dermal
Test: LD50
Result: >2000 mg/kg

Product/substance Alcohols, C9-C11, Ethoxylated



Species: Rat
Route of exposure: Oral
Test: LD50

Result: >2000 mg/kg

Product/substance 2-aminoethanol

Species: Rat
Route of exposure: Oral
Test: LD50
Result: 1720 mg/kg

Product/substance 2-aminoethanol

Species: Rabbit
Route of exposure: Dermal
Test: LD50
Result: 1025 mg/kg

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

▼ Respiratory sensitisation

Product/substance hexyl D-glucoside
Test method: OECD 406

Species: Guinea pig

Description: No sensitation caused

Result: No adverse effect observed (not sensitising)

▼Skin sensitisation

Product/substance Alcohols, C9-C11, Ethoxylated

Test method: OECD 406
Species: Guinea pig
Description: Negative

Result: No adverse effect observed (not sensitising)

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

▼ Long term effects



Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

▼ Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

▼ Other information

None known.

SECTION 12: Ecological information

12.1. ▼ Toxicity

Product/substance potassium hydroxide

Species: Fish

Duration: 24 hours

Test: LC50

Result: 80 mg/L ·

Product/substance 1-methoxy-2-propanol monopropylene glycol methyl ether

Species: Fish
Duration: 96 hours
Test: LC50
Result: 20800 mg/L

Product/substance 1-methoxy-2-propanol monopropylene glycol methyl ether

Species: Daphnia
Duration: 96 hours
Test: EC50
Result: 23300 mg/L

Product/substance 1-methoxy-2-propanol monopropylene glycol methyl ether

Species: Algae
Duration: 72 hours
Test: IC50
Result: >1000 mg/L

Product/substance hexyl D-glucoside

Species: Fish
Duration: 96 hours
Test: LC50
Result: >100 mg/L ·

Product/substance hexyl D-glucoside

Species: Daphnia
Duration: 48 hours
Test: EC50
Result: >100 mg/L ·



Product/substance hexyl D-glucoside

Species: Algae
Duration: 72 hours
Test: EC50
Result: >100 mg/L ·

Product/substance hexyl D-glucoside

Species: Algae
Duration: 72 hours
Test: NOEC
Result: >100 mg/L

Product/substance hexyl D-glucoside

Species: Daphnia
Duration: 21 days
Test: NOEC
Result: >1-10 mg/L

Product/substance Alcohols, C9-C11, Ethoxylated

Species: Fish
Duration: 96 hours
Test: LC50
Result: >1 mg/L

Product/substance Alcohols, C9-C11, Ethoxylated

Species: Daphnia
Duration: 48 hours
Test: EC50
Result: >1 mg/L

Product/substance Alcohols, C9-C11, Ethoxylated

Species: Algae
Duration: 72 hours
Test: EC50
Result: >1 mg/L

Product/substance 2-aminoethanol

Species: Fish
Duration: 96 hours
Test: LC50
Result: 125 mg/L ·

Product/substance 2-aminoethanol Species: Daphnia Duration: 48 hours Test: EC50

Result: 65 mg/L



Product/substance 2-aminoethanol

Species: Algae
Duration: 72 hours
Test: EC50
Result: 2,5 mg/L

12.2. ▼ Persistence and degradability

Product/substance potassium hydroxide Conclusion: Readily biodegradable

Product/substance 1-methoxy-2-propanol monopropylene glycol methyl ether

Result: 96%

Conclusion: Readily biodegradable

Test: OECD 301 E

Product/substance hexyl D-glucoside

Result: >70%

Conclusion: Readily biodegradable

Test: OECD 301 D

Product/substance Alcohols, C9-C11, Ethoxylated Conclusion: Readily biodegradable

Test: OECD 301 D

Product/substance 2-aminoethanol
Conclusion: Readily biodegradable

12.3. ▼ Bioaccumulative potential

Product/substance potassium hydroxide

LogKow: -1,3800

Conclusion: No potential for bioaccumulation

Product/substance 1-methoxy-2-propanol monopropylene glycol methyl ether

LogKow: <3

Conclusion: No potential for bioaccumulation

Product/substance hexyl D-glucoside

Conclusion: No potential for bioaccumulation

Product/substance Alcohols, C9-C11, Ethoxylated Conclusion: No potential for bioaccumulation

Product/substance 2-aminoethanol

LogKow: -1,91

Conclusion: No potential for bioaccumulation

12.4. ▼ Mobility in soil

1-methoxy-2-propanol monopropylene glycol methyl ether LogKoc = 1.699, High mobility potential.



12.5. ▼ Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. ▼Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. ▼ Other adverse effects

None known.

SECTION 13: Disposal considerations

▼ Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)

HP 8 - Corrosive

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

20 01 13* Solvents

▼ Specific labelling

▼ Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 14.2 UN / ID UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informatio n:
ADR	UN1814 POTASSIUM HYDROXIDE SOLUTION	Transport hazard class: 8 Label: 8 Classification code: C5	II	No	Limited quantities: A L Tunnel restriction code: (E) See below for additional information .
IMDG	UN1814 POTASSIUM HYDROXIDE SOLUTION	Transport hazard class: 8 Label: 8 Classification code: C5	II	No	Limited quantities: L EmS: F-A S-B See below for additional information



	14.1 14.2 UN / ID UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informatio n:
IATA	UN1814 POTASSIUM HYDROXIDE SOLUTION	Transport hazard class: 8 Label: 8 Classification code: C5	II	No	See below for additional information

^{*} Packing group

▼ Additional information

This product is within scope of the regulations of transport of dangerous goods.

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

Hazchem Code: 2R

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements.

Control of Major Accident Hazards (COMAH) - Categories / dangerous substances

Not applicable.

▼ UK-REACH, Annex XVII

1-methoxy-2-propanol monopropylene glycol methyl ether is subject to UK-REACH restrictions (entry 40).

Additional information

Not applicable.

Sources

The Management of Health and Safety at Work Regulations 1999.

^{**} Environmental hazards



The Health and Safety at Work etc. Act 1974 Regulations 2013.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

▼ Full text of H-phrases as mentioned in section 3

H226, Flammable liquid and vapour.

H302, Harmful if swallowed.

H312, Harmful in contact with skin.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H332, Harmful if inhaled.

H336, May cause drowsiness or dizziness.

▼ Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

GWP = Global warming potential

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of



1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the substance/mixture in regard of skin corrosion and serious eye damage is based on the pH-criterion given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The safety data sheet is validated by

RO

▼ Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en