

## SAFETY DATA SHEET

### AGS 3550

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Trade name

AGS 3550

Product no.

3550

Unique formula identifier (UFI)

QW70-W0E8-900A-FEAF

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Graffiti protection

Restricted to professional users.

Uses advised against

None known.

##### 1.3. Details of the supplier of the safety data sheet

Company and address

**Trion Tensid AB**

Svederusgatan 1-3

SE-75450 Uppsala

Sweden

+46 18 15 61 90

[www.trion.se](http://www.trion.se)

Contact person

William Stomilovic

E-mail

[info@trion.se](mailto:info@trion.se)

Revision

01/04/2025

SDS Version

8.0

Date of previous version

16/08/2023 (7.0)

##### 1.4. ▼ Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)

General public:

England - Dial 111 to reach NHS 111 (24 hour service)

Scotland - Dial 112 to reach NHS 24 (24 hour service)

Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)

See section 4 "First aid measures".

## SECTION 2: Hazards identification

### 2.1. ▼ Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.

Water-react. 3; H261, In contact with water releases flammable gases.

Acute Tox. 4; H302, Harmful if swallowed.

Skin Corr. 1B; H314, Causes severe skin burns and eye damage.

Eye Dam. 1; H318, Causes serious eye damage.

STOT SE 3; H336, May cause drowsiness or dizziness.

Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

#### Hazard pictogram(s)



#### Signal word

Danger

#### ▼ Hazard statement(s)

Highly flammable liquid and vapour. (H225)

In contact with water releases flammable gases. (H261)

Harmful if swallowed. (H302)

Causes severe skin burns and eye damage. (H314)

May cause drowsiness or dizziness. (H336)

Harmful to aquatic life with long lasting effects. (H412)

#### Precautionary statement(s)

##### General

-

##### Prevention

Do not breathe vapour/mist. (P260)

Wear eye protection/protective gloves/protective clothing. (P280)

##### ▼ Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. (P303+P361+P353)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)

##### Storage

Store in a well-ventilated place. Keep cool. (P403+P235)

##### Disposal

Dispose of contents/container in accordance with local regulation (P501)

#### Hazardous substances

organic polysilazane compound

n-butyl acetate

3-aminopropyltriethoxysilane

#### Additional labelling

EUH066, Repeated exposure may cause skin dryness or cracking.

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

UFI: QW70-W0E8-900A-FEAF

#### VOC

VOC content: 199 g/L

MAXIMUM VOC CONTENT (Phase II, category B/e: 840 g/L)

#### 2.3. Other hazards

##### ▼ Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable. This product is a mixture.

#### 3.2. ▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
organic polysilazane compound	CAS No.: 475645-84-2 EC No.: UK-REACH: Index No.:	60-80%	Flam. Liq. 2, H225 Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412	[19]
n-butyl acetate	CAS No.: 123-86-4 EC No.: 204-658-1 UK-REACH: Index No.: 607-025-00-1	15-25%	EUH066 Flam. Liq. 3, H226 STOT SE 3, H336	[1]
3-aminopropyltriethoxysilane	CAS No.: 919-30-2 EC No.: 213-048-4 UK-REACH: Index No.: 612-108-00-0	1-3%	Acute Tox. 4, H302 Skin Corr. 1B, H314	
2-(2-butoxyethoxy)ethanol diethylene glycol monobutyl ether	CAS No.: 112-34-5 EC No.: 203-961-6 UK-REACH: Index No.: 603-096-00-8	<0.1%	Eye Irrit. 2, H319	
ammonia, anhydrous	CAS No.: 7664-41-7 EC No.: 231-635-3 UK-REACH: Index No.: 007-001-00-5	<0.05%	Flam. Gas 2, H221 Skin Corr. 1B, H314 Acute Tox. 3, H331 Aquatic Acute 1, H400 (M=1)	[1]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

#### ▼ Other information

[1] European occupational exposure limit.

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.  
Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

##### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

##### Skin contact

Flush exposed area with water for a long time - at least 30 minutes. It may be necessary to flush for several hours. Use a comfortable water temperature (20-30 °C). Contact Poison Information/doctor/hospital for further advice on follow-up and treatment.

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

##### Eye contact

If in eyes: Flush eyes with plenty of water or salt water (20-30 °C) for at least 30 minutes and continue until irritation stops. Remove contact lenses. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.

##### Ingestion

In the case of ingestion, contact a doctor immediately. If the person is conscious, give them water. DO NOT try to induce vomiting unless this is recommended by a doctor. Hold head facing down to prevent vomit from returning to the mouth and throat. Prevent shock by keeping the injured person warm and calm. Initiate immediate resuscitation if breathing stops. If unconscious, roll the injured person into recovery position. Call an ambulance.

##### Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

#### 4.2. Most important symptoms and effects, both acute and delayed

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

#### 4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

##### Information to medics

Bring this safety data sheet or the label from this product.

### SECTION 5: Firefighting measures

#### 5.1. ▼ Extinguishing media

Suitable extinguishing media: Dry powder (Class D), sodium chloride (granulate) or dry sand.

Unsuitable extinguishing media: DO NOT USE WATER!

#### 5.2. Special hazards arising from the substance or mixture

Highly flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Nitrogen oxides (NO<sub>x</sub>)  
Carbon oxides (CO / CO<sub>2</sub>)

### 5.3. ▼ Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

Contaminated areas may be slippery.

### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

### 6.3. ▼ Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Do not flush with water or use water-based cleaning agents.

### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating] equipment.

Use non-sparking tools.

Take action to prevent static discharges.

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid direct contact with the product.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

### 7.2. ▼ Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Store in a dry place. Store in a closed container.

#### Recommended storage material

Always store in containers of the same material as the original container.

#### Storage conditions

4 - 25 Celcius

#### ▼ Incompatible materials

Water

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

## SECTION 8: Exposure controls/personal protection

### 8.1. ▼ Control parameters

n-butyl acetate

Long term exposure limit (8 hours) (ppm): 150

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 724

Short term exposure limit (15 minutes) (ppm): 200

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 966

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.  
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

### DNEL

n-butyl acetate

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	102,34 mg/kbm
Long term – Local effects - Workers	Inhalation	480 mg/kbm
Short term – Local effects - General population	Inhalation	859,7 mg/kbm
Short term – Local effects - Workers	Inhalation	960 mg/kbm

### PNEC

n-butyl acetate

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Single	0,18 mg/l
Freshwater sediment	Single	0,981 mg/kg
Marine water	Single	0,018 mg/l
Marine water sediment	Single	0,0981 mg/kg
Soil	Single	0,0903 mg/kg

### 8.2. ▼ Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

#### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

#### Exposure scenarios

There are no exposure scenarios implemented for this product.

#### Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

#### Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Ensure that eyewash stations and safety showers are located within easy reach.  
Apply standard precautions during use of the product. Avoid inhalation of vapours.

#### ▼ Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

#### Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

#### Individual protection measures, such as personal protective equipment


##### Generally

Use only UKCA marked protective equipment.


##### Respiratory Equipment

Type	Class	Colour	Standards	
Combination filter A2B2E2K2-Hg-P3		Brown/Gray/Yellow/Green /Red/White	EN14387	


##### Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	

#### ▼ Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Butyl	0,7	> 240	EN374-2, EN16523-1, EN388, EN421	

##### Eye protection

Type	Standards	
Wear safety glasses with side shields.	EN166	

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Physical state

Liquid

#### Colour

Colourless

#### Odour / Odour threshold

Ammonia odor

#### ▼ pH

No data available.

#### Density (g/cm<sup>3</sup>)

0.97

## ▼ Kinematic viscosity

No data available.

## Particle characteristics

Does not apply to liquids.

## Phase changes

## ▼ Melting point/Freezing point (°C)

No data available.

## Softening point/range (°C)

Does not apply to liquids.

## Boiling point (°C)

127

## ▼ Vapour pressure

No data available.

## ▼ Relative vapour density

No data available.

## ▼ Decomposition temperature (°C)

No data available.

## Data on fire and explosion hazards

## Flash point (°C)

4.5

## Flammability (°C)

The material is ignitable.

## Auto-ignition temperature (°C)

420

## ▼ Lower and upper explosion limit (% v/v)

No data available.

## Solubility

## Solubility in water

Insoluble

## ▼ n-octanol/water coefficient (LogKow)

No data available.

## ▼ Solubility in fat (g/L)

No data available.

## 9.2. Other information

## VOC (g/L)

199

## Other physical and chemical parameters

No data available.

## ▼ Oxidizing properties

No data available.

**SECTION 10: Stability and reactivity**

## 10.1. Reactivity

The product hydrolyses quickly in the presence of water to: Hydrogen, Ammonia (NH<sub>3</sub>), siloxanes

## 10.2. Chemical stability

The product hydrolyses quickly in presence of water to: Hydrogen, Ammonia (NH<sub>3</sub>), and siloxanes. Due to gaseous decomposition products, overpressure can occur in tightly sealed containers.



### 10.3. Possibility of hazardous reactions

Reacts vigorously with water, including moisture in the air. Reacts with: Alcohols, amines: Decomposition under formation of Ammonia

### 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect against direct sunlight.

### 10.5. ▼ Incompatible materials

Oxidising agent, Base, Acid, halogenated constituents.  
Water

### 10.6. Hazardous decomposition products

Hydrogen, Ammonia

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### ▼ Acute toxicity

Product/substance	organic polysilazane compound
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	300-2000 mg/kg ·

Product/substance	n-butyl acetate
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	>10000 mg/kg

Product/substance	n-butyl acetate
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	>17600 mg/kg

Product/substance	n-butyl acetate
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	21,1 mg/L

Product/substance	3-aminopropyltriethoxysilane
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	1780 mg/kg

Product/substance	3-aminopropyltriethoxysilane
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Result: 3800 mg/kg

Harmful if swallowed.

#### Skin corrosion/irritation

Causes severe skin burns and eye damage.

#### Serious eye damage/irritation

Causes serious eye damage.

#### Respiratory sensitisation

Based on available data, the classification criteria are not met.

#### Skin sensitisation

Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

#### Long term effects

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

#### ▼ Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

#### ▼ Other information

None known.

## SECTION 12: Ecological information

### 12.1. ▼ Toxicity

Product/substance	organic polysilazane compound
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	57,1 mg/L ·

Product/substance	n-butyl acetate
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	18 mg/L

Product/substance	n-butyl acetate
-------------------	-----------------

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Species:	Algae
Duration:	72 hours
Test:	EC50
Result:	675 mg/L

Product/substance	n-butyl acetate
Species:	Crustacean
Duration:	48 hours
Test:	EC50
Result:	44 mg/L

Product/substance	3-aminopropyltriethoxysilane
Species:	Algae
Duration:	72 hours
Test:	EC50
Result:	603 mg/L

Product/substance	3-aminopropyltriethoxysilane
Species:	Crustacean
Duration:	48 hours
Test:	EC50
Result:	331 mg/L

Harmful to aquatic life with long lasting effects.

#### 12.2. ▼ Persistence and degradability

Product/substance	n-butyl acetate
Result:	98%
Conclusion:	Readily biodegradable
Test:	OECD 301 D

Product/substance	3-aminopropyltriethoxysilane
Conclusion:	Readily biodegradable

#### 12.3. ▼ Bioaccumulative potential

Product/substance	n-butyl acetate
BCF:	15
LogKow:	1,7800
Conclusion:	No potential for bioaccumulation

Product/substance	3-aminopropyltriethoxysilane
LogKow:	0,3100
Conclusion:	No potential for bioaccumulation

#### 12.4. Mobility in soil

No data available.

#### 12.5. ▼ Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

#### 12.6. ▼ Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

#### 12.7. Other adverse effects

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

## SECTION 13: Disposal considerations

### 13.1. ▼Waste treatment methods

Product is covered by the regulations on hazardous waste. (\*)

HP 3 - Flammable

HP 6 - Acute toxicity

HP 8 - Corrosive

HP 14 - Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Do not mix with aqueous wastes or wastes containing protic substances. Dispose of the product in accordance with the standards of the relevant waste disposal authorities or of an approved waste disposal site. Keep any consultation with the waste management authority or other competent authority. Do not allow product waste to come into surface water or drainage. Ensure that product residues do not enter the soil.



#### ▼EWC code

08 01 11\* Waste paint and varnish containing organic solvents or other dangerous substances

#### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

## SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN3129	WATER-REACTIVE LIQUID, CORROSIVE, N.O.S. (organic polysilazane compound, n-butyl acetate)	Transport hazard class: 4.3 Label: 4.3+8 Classification code: WC1 	II	No	Limited quantities: 500 ml Tunnel restriction code: 0(D/E) See below for additional information .
IMDG	UN3129	WATER-REACTIVE LIQUID, CORROSIVE, N.O.S. (organic polysilazane compound, n-butyl acetate)	Transport hazard class: 4.3 Label: 4.3+8 Classification code: WC1 	II	No	Limited quantities: 500 ml EmS: F-G S-N See below for additional information .
IATA	UN3129	WATER-REACTIVE LIQUID, CORROSIVE, N.O.S. (organic polysilazane compound, n-butyl acetate)	Transport hazard class: 4.3 Label: 4.3+8 Classification code: WC1	II	No	See below for additional

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
					information

\* Packing group

\*\* Environmental hazards

#### ▼ Additional information

This product is within scope of the regulations of transport of dangerous goods.

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

#### 14.6. Special precautions for user

Not applicable.

#### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restrictions for application

Restricted to professional users.

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

#### Demands for specific education

No specific requirements.

#### ▼ SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes ammonia, anhydrous

#### ▼ REACH, Annex XVII

organic polysilazane compound is subject to UK-REACH restrictions (entry 40).

n-butyl acetate is subject to UK-REACH restrictions (entry 40).

#### Additional information

Not applicable.

#### ▼ Sources

The Management of Health and Safety at Work Regulations 1999.

The Health and Safety at Work etc. Act 1974 Regulations 2013.

Control of Major Accident Hazards (COMAH) Regulations 2015.

2012 No. 1715 ENVIRONMENTAL PROTECTION: The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as

retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

#### 15.2. Chemical safety assessment

No

### SECTION 16: Other information

#### ▼ Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.

H221, Flammable gas.

H225, Highly flammable liquid and vapour.

H226, Flammable liquid and vapour.

H302, Harmful if swallowed.

H314, Causes severe skin burns and eye damage.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H331, Toxic if inhaled.

H336, May cause drowsiness or dizziness.

H400, Very toxic to aquatic life.

H412, Harmful to aquatic life with long lasting effects.

#### ▼ Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

GWP = Global warming potential

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

---

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

#### Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental data.

#### The safety data sheet is validated by

RO

#### ▼ Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en