



AGS 1

ART.NO: 3615 | GRAFFITI REMOVER



AGS 1 is a powerful graffiti and paint remover. For use on exterior and interior surfaces. For use on hard, non-porous surfaces and painted surfaces. It is **biodegradable** and also approved by **Good Environmental Choice**, making it a sustainable option for both the environment and workplace.

AGS 1 removes most types of graffiti from both marker and spray paint. We recommend testing a small area first. **AGS 1** is safe to use on most surfaces, except plexiglass and certain plastics.

INSTRUCTIONS FOR USE

Hard surfaces

Apply **AGS 1** on to a dry, clean rag or an absorbent paper towel and wipe away the graffiti. Turn over the cloth so that only the clean part is used to the graffiti. Avoid wiping over dissolved graffiti. Remove any AGS 1 residue using water or a general cleaner to neutralize any chemical remnants on the surface. It is always recommended to make a test on a small part of the surface.

Porous surfaces

Apply **AGS 1** with a low pressure sprayer. Let dwell for 5-10 minutes. Jet off with hot water and high pressure, (90°C, 150 bar/2175 PSI). Lance nozzle spread should be 15 - 25 degrees and water flow should be 15 to 20 litres/minute. If pigment shadows remain, use **AGS 60** or **AGS 65**.

Dosage

Use as concentrate.

Consumption

0,2-0,5 litre/m².

Storage

Store frost-free in original closed container.

Shelf life

Approximately 24 months in unopened container.

Precautions

Use protective gloves and glasses.

Technical data

- Pale yellow liquid with a thin consistency.
- Packaging: 5 and 25-liter plastic containers.
- Density: 1.05 kg/liter.
- Subtle scent.
- Flash point around 100°C.
- Contains no substances requiring labeling

Not classified as dangerous goods according to **ADR**. For more information, see **MSDS**