



BPS 7726

ART. NO: 7726 | HYDROPHOBATION OF CONSTRUCTION CONCRETE

Silane-based impregnating agent for concrete. Approved in accordance with EN 1504-2:2004, AMA Specification 26, LFB.311. Effectively prevents water and salt penetration. Vapour-permeable, i.e. allows the surface to breathe. High penetration capacity.

BPS 7726 is a silane based facade hydrophobation protection for use on concrete and reinforced concrete. **BPS 7726** consists of "small molecules" contributing to a deep penetration. **BPS 7726** effectively protects the surface against water and salt ingress. **BPS 7726** is permeable, i.e. water cannot penetrate, but the surface "can breathe" and release moisture. **BPS 7726** is approved according to EN 1504-2, alone and in combination with [AGS 3502](#) graffiti protective coating.

Instructions for use

Secure that the surface is clean from traffic grime, soot, grease and oil based mould release. Fresh concrete have to cure for at least 28 days prior to treatment with **BPS 7726**. Apply **BPS 7726** with a low pressure sprayer, roller or a brush to secure a minimum consumption of 0,3 l/m². Apply 2 times, wet on wet. For best hydrophobation effect, ensure that the surface is dry. Drying time after cleaning with high pressure and water is approximately 24-72 hours (In cold wether condition the dry time can be increased up to 7 days). Lowest application temperature is approximately +2°C.

Dosage

Use as concentrate.

Consumption

Normal usage: approximately 0,3 litre/m² depends on surface absorption capacity. Old concrete may require more product, in this case apply 3 applications "wet on wet", and 0,4-0,5 litre/m².

Storage

Store frost-free in original container.

Shelf life

12 months in unopened container.

Safety precautions

Use protective gloves, clothes and glasses.

Technical data

- Transparent liquid with alcoholic odour.
- Packaging: 25 litre plastic jerricans.
- Density: 0,88 kg/litre.
- Flash point >40°C.

Marking

Warning



Flammable liquid and vapour.

Not classified as dangerous goods according **ADR**.
For more information, see [MSDS](#).

Modified: 2026-08-28

This product information is intended as a guide for use of this product. TRION TENSID AB cannot give any guarantee for end result achieved. Applicator of product shall carry out testing and are responsible for the result.